

AR (heating)

Heating capacity (kW)							
air temp [°C]	return temperature [°C]						
	20	25	30	35	40	45	50
	delivery temperature [°C]						
	30	35	40	45	50	55	60
-20	27,30	26,50	25,70	24,90	24,90	24,60	24,30
-19	27,54	26,75	25,95	25,16	25,08	24,77	24,46
-18	27,78	26,99	26,21	25,42	25,26	24,94	24,62
-17	28,02	27,24	26,46	25,68	25,44	25,11	24,78
-16	28,26	27,49	26,71	25,94	25,62	25,28	24,94
-15	28,50	27,73	26,97	26,20	25,80	25,45	25,10
-14	28,98	28,15	27,33	26,50	26,04	25,70	25,36
-13	29,46	28,57	27,69	26,80	26,28	25,95	25,62
-12	29,94	28,99	28,05	27,10	26,52	26,20	25,88
-11	30,42	29,41	28,41	27,40	26,76	26,45	26,14
-10	30,90	29,83	28,77	27,70	27,00	26,70	26,40
-9	31,53	30,44	29,36	28,27	27,47	27,20	26,93
-8	32,17	31,06	29,94	28,83	27,93	27,70	27,47
-7	32,80	31,67	30,53	29,40	28,40	28,20	28,00
-6	33,19	32,13	31,06	30,00	28,82	28,52	28,22
-5	33,58	32,59	31,59	30,60	29,24	28,84	28,44
-4	33,97	33,04	32,12	31,20	29,67	29,17	28,67
-3	34,36	33,50	32,65	31,80	30,09	29,49	28,89
-2	34,74	33,96	33,18	32,40	30,51	29,81	29,11
-1	35,13	34,42	33,71	33,00	30,93	30,13	29,33
0	35,52	34,88	34,24	33,60	31,36	30,46	29,56
1	35,91	35,34	34,77	34,20	31,78	30,78	29,78
2	36,30	35,80	35,30	34,80	32,20	31,10	30,00
3	36,62	36,19	35,77	35,34	32,82	31,71	30,60
4	36,94	36,59	36,23	35,88	33,44	32,32	31,20
5	37,26	36,98	36,70	36,42	34,06	32,93	31,80
6	37,58	37,37	37,17	36,96	34,68	33,54	32,40
7	37,90	37,77	37,63	37,50	35,30	34,15	33,00
8	38,08	37,95	37,83	37,70	35,59	34,47	33,35
9	38,25	38,13	38,02	37,90	35,88	34,79	33,70
10	38,60	38,53	38,47	38,40	36,40	35,45	34,50
11	38,74	38,67	38,61	38,54	36,64	35,70	34,76
12	38,88	38,81	38,75	38,68	36,88	35,95	35,02
13	39,02	38,95	38,89	38,82	37,12	36,20	35,28
14	39,16	39,09	39,03	38,96	37,36	36,45	35,54
15	39,30	39,23	39,17	39,10	37,60	36,70	35,80

